

An abstract graphic consisting of several thin, white, parallel lines that originate from the bottom left and extend towards the top right corner of the page. The lines are slightly curved and vary in length, creating a sense of movement and depth against the solid blue background.

CCTV DIRECT

HiLook 4 Ch ColourVu Kit 20m Full Colour Night Vision

HiLook 4 Channel 1080P
ColorVu Kit

HiLook
By HIKVISION

ColorVu
Technology



1080P

500GB

RG59
100M

CCTV DIRECT

Colour Night vision - HiLook by
Hikvision 4ch Turbo HD kit - 4 x 1080p
ColorVu cameras - 20m Full colour
night vision - 500GB HDD - 100m
Cable

R 4,995.00

Colour Night vision - HiLook by Hikvision 4ch Turbo HD kit - 4 x 1080p ColorVu cameras - 20m Full colour night vision - 500GB HDD - 100m Cable

Kit Includes

1 x HiLook DVR-104Q-F1 4 channel TVI 1080P Lite Hybrid DVR With Smartphone and PC viewing

4 x HiLook *THC-B129P Full colour night vision 1080p camera*

1 x 500GB SATA Hard Drive

8 x BNC Plug

4 x DC plugs

1 x 12VDC 5A Power Supply

1 x 100m Cable RG59 Co-Axial

No Screen



2MP 1080p Full colour night vision camera

2.8mm wide angle lens

IP66 weatherproof

20m Night vision



HiLook

Video Input and Transmission

- Connectable to Turbo HD/HDCVI/AHD/CVBS signal input
- Up to 1-ch 960p IP cameras input
- Long distance transmission over UTP and coaxial cable

Compression and Recording

- One-key enable H.264+ compression to improve encoding efficiency by up to 50% and reduce data storage costs
Supports real-time 1080p lite and when enabled, the image effect is similar with 1080p

Video Output

HDMI/VGA output at up to 1920 × 1080 resolution

Storage and PlaybackOne SATA interface (up to 6TB capacity per HDD)

- 4/8/16-ch synchronous playback
- Smart search for efficient playback

Smart Function

- Supports multiple VCA (Video Content Analytics) events for both analogue and smart IP cameras
- VQD (Video Quality Diagnostics)
- Unlock pattern for device login for the admin and clear-text password available
- GUID file can be exported for password resetting and imported for finding the forgotten password
- Supports PTZ control via Omnicast VMS of Genetec protocol
- Network & Ethernet Access
- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- One self-adaptive 10/100Mbps network interface
- Output bandwidth limit configurable