



# CCTV DIRECT - SECURE 24/7

HiLook 4 Ch Turbo Kit - DVR - 4 x HD1080P Camera



HiLook by Hikvision 4ch Turbo HD kit -  
DVR - 4 x HD1080P Camera - 20M  
Night vision - 500GB HD - 100m Cable

R 3,750.00

HiLook by Hikvision 4ch Turbo HD kit - DVR - 4 x  
HD1080P Camera - 20M Night vision - 500GB HD - 100m  
Cable



#### Kit Includes

- 1 x HiLook DVR-104Q-F1 4 channel TVI 1080P Lite Hybrid DVR With Smartphone and PC viewing
- 4 x HiLook *THC-B120*: 2MP EXIR Bullet Camera, 20m IR Distance, IP66
- 1 x 500GB SATA Hard Drive
- 8 x BNC Plug
- 4 x DC plugs
- 1 x 12VDC 5A Power Supply
- 1 x 100m Cable RG59 Co-Axial
- No Screen



THC-B120     2 MP EXIR Bullet Camera

- 2 MP high-performance CMOS
- 1920 × 1080 resolution
- 3.6 mm
- Day/Night switch
- EXIR 2.0, smart IR, up to 20 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66



DVR-104G-F1 Turbo HD DVR

Easy connection to your mobile with Hikvision Hik-connect bar code scanning, without any technical or port forwarding knowledge. Includes free iPhone, android, PC and Mac remote viewing software

- Connectable to Turbo HD/HDCVI/AHD/CVBS signal input
- Long distance transmission over UTP and coaxial cable
- One-key enable H.264+ compression to improve encoding efficiency by up to 50% and reduce data storage costs
- Supports 1080p lite and when enabled, the image effect is similar with 1080p
- Simultaneous HDMI/VGA output at up to 1920 × 1080 resolution
- One SATA interface (up to 6 TB capacity per HDD)
- Smart search for efficient playback

### **Video/Audio Input**

---

Audio Input: 1-ch

---

Video Compression: H.264,H.264+

Analog Video Input:	4-ch
Analog and HD-TVI video input:	Support HDTVI input: 1080p25, 1080p30, 720p25, 720p30
Supported camera types:	Support AHD input : 1080p25, 1080p30, 720p25, 720p30 Support HDCVI input: 1080p25, 1080p30, 720p25, 720p30 Support CVBS input
IP Video Input:	1-ch Up to 960P resolution
Video Input Interface:	BNC (1.0 Vp-p, 75Ω)
Audio Compression:	G.711u
Audio Input Interface:	RCA (2.0 Vp-p, 1 kΩ)
Two-way Audio:	1-ch RCA(2.0Vp-p, 1kΩ)

### Video/Audio Output

HDMI/VGA Output:	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Recording resolution:	When 1080p Lite mode not enabled: 720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
Frame Rate:	Main stream: When 1080p lite mode enabled: 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) When 1080p lite mode not enabled: For 720p stream access: 720p/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) For SD stream access: WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Sub-stream: CIF/QVGA/QCIF@25fps (P)/30fps (N)

Video Bit Rate:	32 Kbps ~ 4 Mbps
Stream Type:	Video/Video & Audio
Audio Output:	1-ch RCA(Linear, 1kΩ)
Dual Stream:	Support
Synchronous Playback:	4-ch

### Network management

Remote connections:	32
Network protocols:	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP?, HTTPS

### Hard Disk Driver

Interface Type:	1 SATA Interface
Capacity:	Up to 6 TB capacity for each disk

### External Interface

Network Interface:	1; 10M / 100M self-adaptive Ethernet interface
USB Interface:	2 USB 2.0 Interfaces

